

Avantopool Kinos Plus




Kinos Plus is a transportable pool for cold & warm water therapy and professional level cold recovery – always ready for use. Kinos Plus is 20 cm longer than Kinos, enabling taller people to get full body immersion. The tub is a single piece molded construction made of gelcoated fiberglass. The stairs and railings can be installed either on the sides or the end of the pool.

The Kinos Plus pool's water filtration and automatic continuous ozone purification ensure that the water is always clean. The pool's energy efficiency keeps operating costs down. Using the smart "sleep mode" for example during the nights, the electricity consumption can be reduced significantly (30-40%). The pool's highly effective insulation makes sure that maintaining a constant water temperature is cost-effective.

| Recommended accessories | Ref. |
|-------------------------|--------|
| Filter 5 pack | KSU05P |
| Filter 18 pack | KSU18P |
| Kinos Care package | KHU001 |

Available in 2 basic colors:
white, black

HS Code
85161080



| Product name | Product code | EAN | Export carton meas. |
|--------------------|--------------|---------------|------------------------|
| Kinos Plus (white) | AP002W | 6429810465214 | 145 x 85 x 123, 185 kg |
| Kinos Plus (black) | AP002B | 6429810465207 | 145 x 85 x 123, 185 kg |

Technical details

| | |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions without steps | Length 140 cm, width 79 cm, height 105 cm |
| Dimensions with steps | Length 140/174 cm, width 79/113 cm, height 122 cm |
| Capacity | 320 l |
| Weight when empty | 160 kg (with rails and stairs) |
| Weight when filled | 480 kg |
| Power supply | 230V/50Hz, single-phase. Equipped with a residual current device (RCD) in the supply cord |
| Temperature range | Adjustable between +4°C and +38°C |
| Cooling / heating speed | 3-4°C / hour |
| Current (max) | 7 A |
| Cooling/heating electrical power | 0.7 kW / 1.5 kW |
| Refrigerant | R290 |
| GWP value | Zero |
| Control | Digital control with touch screen, equipped with a temperature-sensitive cold therapy timer |
| Hygiene | Water filtration and continual ozone purification |
| Outdoor use | Only when fully weather-protected |
| Average power consumption | Approximately 5 kWh/day once the pool has reached the target temperature |
| Warranty (limited) | 3 years: pool (basin), steel frame, rails, side panels, piping Private use 2 years / commercial use 1 year: Mechanical and automation components |